

Technical Specification



Product Code: CCA201 **Description:** 45A 1 Gang Double Pole Plate Switch With Neon





General Information

Plate Dimensions (mm) 86 (W) x 86 (H) x 9.5 (D)

Plate Fixing Centres - Horizontal (mm) 60.3

> Style Rounded Profile Finish Polar White

Materials Front Plate & Rocker Switch: Urea

> Neon Lens: Polycarbonate Terminal Screws: Steel & Yellow Passivated

Internal Busbars: Formed Pressed Brass

Yes

Frequency (Hz) 50

Terminal Torque Value (Nm) 2.5

Rear Housing: Nylon

Earth Strap: Mild Steel

Indicator Colour Red

Contacts: Silver "on-lay" Copper / Brass

Terminals: Brass

Rated Voltage (V~) (Ue) 250 Resistive Load Rating (A) 45 **Termination Type** Screw

> Terminal Size (mm) 016

Terminal Capacity - Solid (mm²) 1 x 16

Anti Microbial Certified

Double Pole Switch Twin Earth Terminals

> Neon Indicator Yes

Product Marking On, Off

Minimum Back Box Depth (mm) 35 Ingress Protection IP20

Operational Temperature (°C) -5 to +40

Warranty (Years)

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal. All white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases as well as anti-viral properties against enveloped and non-enveloped viruses.

All products have been independently tested with 99.9% of enveloped viruses and 92% of nonenveloped viruses killed off whilst achieving a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.

