

Technical Specification



Product Code: CMA100

	,	8
Shavers only		
General Information		
Plate Dimensions (mm)	86 (W) x 146 (H) x 9.5 (D)	
Plate Fixing Centres - Horizontal (mm)	120.6	
Style	Rounded Profile	
Finish	Polar White	
Materials	Front Plate: Urea	Rear Housing: Urea
	Terminals: Brass	Terminal Screws: Steel & Yellow Passivated
	Contacts: Silver "on-lay" Copper / E	Brass Internal Busbars: Formed Pressed Brass
	Earth Strap: Mild Steel	
Anti Microbial Certified	Yes	
Rated Voltage (V~) (Ue)	240	Frequency (Hz) 50/60
Load Rating @115V (Va)	20	
Load Rating @230V (Va)	20	
Thermal Protection Device	PTC Resettable Fuse	
Termination Type	Screw	
Terminal Size (mm)	Ø3.5	Terminal Torque Value (Nm) 0.5
Terminal Capacity - Solid (mm ²)	2×1.5 or 1×2.5	
Socket Features	Safety Interlock Shutter	
Twin Earth Terminals	Yes	
Product Marking	Shavers Only, 230V~, 115V~ 47	
Minimum Back Box Depth (mm) Ingress Protection	IP21	
Operational Temperature (°C)	-5 to +40	
Warranty (Years)	20	
Additional Information For cleaning / polishing of products, use only a soft, dry, clean cloth. This outlet is not continuously rated and therefore not suitable for use as a permanent charging outlet. CLICK dual voltage shaver outlets incorporate a double wound isolating transformer rated 20Va at 230V or 115V and meets BS EN 61558-2-5:2010 making it safe for use in bathrooms. PTC resettable fuses increase resistance as temperature increases due to increased flow. PTC resettable fuses are designed to limit unsafe currents while allowing constant safe current levels, resistance will "reset" automatically when the fault is removed and temperature returns to a safe level. Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal. All white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases as well as anti-viral properties against enveloped and non-enveloped viruses. All products have been independently tested with 99.9% of enveloped viruses and 92% of non-enveloped viruses killed off whilst achieving a 99.9% kill rate across all four types of the strains of bacteria.		

Description: 115V/230V Dual Voltage Shaver Socket Outlet

bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.

OC ECK

Scolmore House, Mariner, Lichfield Road Industrial Estate, Tamworth, Staffordshire, B79 7UL United Kingdom **T**: +44 (0)1827 63454 | **F**: +44 (0)1827 63362 **E**: sales@scolmore.com | **W**: scolmore.com

Page 1 of 1 (18/02/22) Errors & Omissions excluded. Specification is subject to change without notice.