

## **Technical Specification**



Product Code: CMA161 Description: 1 Gang 2 Way 100W Dimmer Switch





Rear Housing: Nylon

Frequency (Hz)

Terminal Torque Value (Nm) 0.25

Terminal Screws: Steel & Yellow Passivated

50

## **General Information**

Plate Dimensions (mm) 86 (W) x 86 (H) x 9.5 (D)

Plate Fixing Centres - Horizontal (mm) 60.3

> Style Rounded Profile Finish Polar White Materials Front Plate: Urea Terminals: Brass

> > PCB: Mixed Components

Anti Microbial Certified Rated Voltage (V~) (Ue) 250 Load Rating (W) 5 - 100

Load Rating Comments Suitable For LED

Terminal Size (mm) 035

Terminal Capacity - Solid (mm²) 2 x 1.5

2 Way Switch

Switch Control Type Press - ON/OFF, Rotate - Dim

Dimmer Technology Type Trailing Edge

Minimum Back Box Depth (mm) 25 Ingress Protection IP20 Operational Temperature (°C) -5 to +40

Warranty (Years)

Warranty - Electronics (Years) 1

## **Additional Information**

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal. All white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases as well as anti-viral properties against enveloped and non-enveloped viruses.

All products have been independently tested with 99.9% of enveloped viruses and 92% of nonenveloped viruses killed off whilst achieving a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.

## **Compatible Dimmer Modules**

MD9014: 100W Dual Mode LED Dimmer Module

MD9001: 6A Push ON/OFF (Dummy Dimmer / Non Dimmable) Module

MD9010: 1-10V Analogue Rotary Dimmer Module MD9022: 40-250W Leading Edge Dimmer Module MD9042: 60-400W Leading Edge Dimmer Module



