





Product Code: CMA162

Description: 2 Gang 2 Way 100W Dimmer Switch

General Informatio	n	
Plate Dimensions (mm		
Plate Fixing Centres - Horizontal (mm	, , , , ,	
Styl		
Finis		
Materia		Rear Housing: Nylon
	Terminals: Brass	Terminal Screws: Steel & Yellow Passivated
	PCB: Mixed Compone	ents
Anti Microbial Certifie	d Yes	
Rated Voltage (V~) (Ue		Frequency (Hz) 50
Load Rating (W		
Load Rating Comment		
Terminal Size (mm	,	Terminal Torque Value (Nm) 0.25
Terminal Capacity - Solid (mm 2 Way Switc		
Switch Control Typ		te - Dim
Dimmer Technology Typ		
Minimum Back Box Depth (mr		
Ingress Protectio		
Operational Temperature (°C	<b>c)</b> -5 to +40	
Warranty (Years	<b>s)</b> 20	Warranty - Electronics (Years) 1
Additional InformationFor cleaning / polishing of products, use only a soft, dry, clean cloth. Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal. 		
Compatible Dimmer Modules MD9014: 100W Dual Mode LED Dimmer Module MD9001: 6A Push ON/OFF (Dummy Dimmer / Non Dimmable) Module MD9010: 1-10V Analogue Rotary Dimmer Module MD9022: 40-250W Leading Edge Dimmer Module MD9042: 60-400W Leading Edge Dimmer Module		

Scolmore House, Mariner, Lichfield Road Industrial Estate, Tamworth, Staffordshire, B79 7UL United Kingdom T: +44 (0)1827 63454 | F: +44 (0)1827 63362 E: sales@scolmore.com | W: scolmore.com

Page 1 of 1 (18/02/22) Errors & Omissions excluded. Specification is subject to change without notice.

НII