





Technical Specification

Product Code: CMA171

Description: 10AX 1 Gang 2 Way Architrave Switch (File) **General Information** Plate Dimensions (mm) 32 (W) x 86 (H) x 9.5 (D) Plate Fixing Centres - Horizontal (mm) 60.3 MiniGrid Plate (Gang) 1 MiniGrid Single Width Module Quantity 1 MiniGrid Double Width Module Quantity 0 **Rounded Profile** Style Finish Polar White Materials Front Plate & Rocker Switch: Urea Rear Housing: Nylon Terminals: Brass Terminal Screws: Steel & Yellow Passivated Contacts: Silver "on-lay" Copper / Brass Internal Busbars: Formed Pressed Brass Anti Microbial Certified Yes Rated Voltage (V~) (Ue) 250 Frequency (Hz) 50 Inductive Load Rating (AX) 10 Load Rating Comments Suitable for Inductive Loads Termination Type Screw Terminal Size (mm) Terminal Torque Value (Nm) 0.5 Ø3.5 Terminal Capacity - Solid (mm²) 2 x 1.5 Modular Rocker Switches Yes 2 Way Switch Yes Minimum Back Box Depth (mm) 25 Ingress Protection IP20 Operational Temperature (°C) -5 to +40 Warranty (Years) 20 Additional Information For cleaning / polishing of products, use only a soft, dry, clean cloth. Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal. All white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases as well as anti-viral properties against enveloped and non-enveloped viruses. All products have been independently tested with 99.9% of enveloped viruses and 92% of nonenveloped viruses killed off whilst achieving a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae. Interchangeable with modules in the MiniGrid Range. **MINIGRID®** Suitable flush mounting back box WA671 or surface pattress CMA075

CECA

Page 1 of 1 (18/02/22) Errors & Omissions excluded. Specification is subject to change without notice.