


## **Technical Specification**

Product Code: CMA204 Description: 45A 2 Gang Double Pole Switch With 13A Double Pole Switched Socket





## **General Information**

Plate Dimensions (mm) 146 (W) x 86 (H) x 9.5 (D)

Plate Fixing Centres - Horizontal (mm) 120.6

> Rounded Profile Style Finish Polar White

Materials Front Plate & Rocker Switch: Urea Rear Housing: Urea

Terminals: Brass Terminal Screws: Steel & Yellow Passivated Contacts: Silver "on-lay" Copper / Brass Internal Busbars: Formed Pressed Brass

Earth Strap: Mild Steel

Anti Microbial Certified

Rated Voltage (V~) (Ue) 250 Frequency (Hz)

Resistive Load Rating (A) 45 Termination Type Screw

Terminal Size (mm) 06 Terminal Torque Value (Nm) 2.5

Terminal Capacity - Solid (mm<sup>2</sup>) 1 x 16 Double Pole Switch Twin Earth Terminals Yes

> Product Marking On, Off, Socket, Cooker

Minimum Back Box Depth (mm) Ingress Protection

Operational Temperature (°C) -5 to +40

Warranty (Years)

Additional Information For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal. All white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases as well as anti-viral properties against enveloped and non-enveloped viruses.

All products have been independently tested with 99.9% of enveloped viruses and 92% of nonenveloped viruses killed off whilst achieving a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.



