


Technical Specification



Product Code: CMA606 Description: New Media™ Part Furnished Front Plate - 4 x 13A DP Switched Socket

Outlets & Apertures



General Information

Plate Dimensions (mm) $250 \text{ (W)} \times 216 \text{ (H)} \times 8 \text{ (D)}$

New Media Aperture Dimensions (mm) 75 x 50 (x2)

New Media Module Quantity Accepts Upto 2 Rows of 3 x 25mm x 50mm Modules

Style Mode Finish Polar White

Materials Front Plate & Rear Housing: Urea Terminals: Brass

Terminal Screws: Steel & Yellow Passivated Contacts: Silver "on-lay" Copper / Brass

Internal Busbars: Formed Pressed Brass Earth Strap: Mild Steel

Anti Microbial Certified No

Rated Voltage (V~) (Ue) 250 Frequency (Hz) 50

Resistive Load Rating (A) 13 Termination Type Screw

Terminal Size (mm) Ø5 Terminal Torque Value (Nm) 2.5

Terminal Capacity - Solid (mm²) 3 x 2.5 or 2 x 4

Double Pole Switch Yes
Twin Earth Terminals Yes

Compatible Back Box (mm) MP535 (35) Or MP525 (47)

Ingress Protection IP20
Operational Temperature (°C) -5 to +40
Warranty (Years) 10

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit

diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Requires MP525 or MP535 flush back box.

Interchangeable with modules in the New Media Range.

