

## SPECIFICATION SHEET

Product Code **CMA770AG**

Description **13A 2 Gang Switched Socket Outlet with Single USB Charging Outlet**



| General Information  |  |
|----------------------|--|
| Dimensions           | 146mm x 86mm x 9.5mm   |
| Material composition | Front Plate: Urea<br>Rear Housing: Urea<br>Terminals: Brass<br>Terminal Screws: Steel and Yellow Passivated<br>Earth Strap: Mild Steel<br>Internal Busbars: Formed Pressed Brass<br>PCB: Mixed Components<br>Silver "on-lay" copper/brass contacts |
| Back Box Depth       | 25mm – 47mm  |
| Cable Size           | L & N = Up to 3 x 2.5mm <sup>2</sup> solid or stranded, or up to 2 x 4mm <sup>2</sup> stranded conductors.<br>Earth = Up to 3 x 1.5mm <sup>2</sup> or 2.5mm <sup>2</sup> solid or stranded, or up to 2=2 x 4mm <sup>2</sup> stranded conductors    |
| Terminal Size        | Live: 5mm<br>Neutral: 5mm<br>Earth: 5mm  |
| Switched             | Yes  |
| Double Pole          | No (Single Pole)   |
| Twin Earth           | Yes  |
| USB Charging Outlet  | 5V DC, 2.1A  |
| USB Output Connector | USB Type "A"   |
| USB Standby Current  | 2mA  |
| Warranty             | 1 Year   |

| Standards  |
|--|
| BS 5733 (BS 1363-2)<br>BS EN 60950-1 (USB Charger)<br>EN 61000-6-1/3, EN 61204-3 (EMC Directive) |

| Additional Information   |
|--|
| Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram supplied with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.<br><br>All white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases. All products independently tested achieved a 99.9% kill rate across all four types of the strains of bacteria – MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae |