

Product Code: CSPGM2075BK

Description: Smart GridPro Scenario Switch



General Information

Dimensions (mm)	24.5 (W) x 50 (H) x 22.5 (D)	
Finish	Black	
Insert Colour	Black	
Materials	Body & Insert: Nylon	Switch: Polycarbonate
Rated Voltage (DC)	3	
Battery Type	CR 2032 (Supplied)	
Battery Lifetime (Approx.)	300 Days (Dependent On Use)	
Protocol	Zigbee	Signal Transmission Frequency 2.4GHz
Open Air Wireless Range (M)	<50	
Indicator Colour	Blue	
Minimum Back Box Depth (mm)	25 (35 Flat Plate)	
Ingress Protection	IP20	
Working Humidity	0%-90%RH	
Operational Temperature (°C)	-5 to +40	
Warranty (Years)	2	

Standards	BS EN 62368-1 BS EN 62479 BS EN 50663 ETSI EN 301 489-1 ETSI EN 301 489-17 & EN 300 328 V2.2.2
------------------	--

Components Supplied Smart Scenario Switch, CR 2032 Battery, Reset Key, Instruction Manual

Installation Overview Utilises inserts and plates in the GridPro range
Wireless pairs to ClickSmart+ app
Single and multiple presses can be set to activate devices via the app "Tap To Run" setup

Programming Information With hub and app setup with sensor having battery installed, using the pin supplied press the reset button for five seconds and the sensor LED will start flashing. Must be paired with hub via app.