

SPECIFICATION SHEET

Product Code

DP*570#

Description

13A 2 Gang 'Ingot' Switched Socket Outlet with Single USB Charging Outlet



General Information	
Dimensions	148mm x 88mm x 8mm (Excluding Gasket)
Finishes Available	Replace * with: AB (Antique Brass), BN (Black Nickel), BR (Polished Brass), CH (Polished Chrome), SB (Satin Brass), SC (Satin Chrome) or SS (Stainless Steel)
Inserts Available	Replace # with: WH (White) or BK (Black). Black or White gasket supplied to match appropriate insert. (Antique Brass and Black Nickel are only available with black inserts)
Material composition	Front Plate: Stainless Steel Rear Housing: Nylon (PA66) Terminals: Brass Earth Strap: Mild Steel Terminal Screws: Steel and Yellow Passivated Internal Busbars: Formed Pressed Brass PCB: Mixed Components Silver "on-lay" copper/brass contacts
Voltage	250V~ 50Hz
Load Rating	13A
Terminal Size	5mm \varnothing
Torque Value	2.5Nm
Cable Size	4 x 2.5mm ²
Back Box Depth	25mm – 47mm
Switched	Yes
Double Pole	No (Single Pole)
Twin Earth Terminals	Yes
USB Charging Output	5V DC, 2.1A
USB Output Connector	USB Type "A"
USB Standby Current	2mA
Operational Temperature	-5°C – +40°C
Warranty	10 Years
Standards	
	BS 1363-2: 1995 + A4: 2012
Additional Information	
	Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram supplied with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Errors & Omissions excluded. Specification is subject to change without notice.

V1.0