

Product Code: DPBR660

Description: 20A Double Pole 1 Gang Plate Key Lockable Switch



Representative Image

**General Information**

<b>Dimensions</b>	88mm (W) x 88mm (H) x 8mm (D)
<b>Dimensions With Gasket</b>	91mm (W) x 91mm (H) x 9mm (D)
<b>Plate Design &amp; Finish</b>	Rounded Profile Polished Brass
<b>Gasket Colour</b>	Supplied With Both Black & White Gasket
<b>Materials</b>	Front Plate: Stainless Steel Insert: Urea Earth Plate & Yoke: Mild Steel Terminals: Brass Terminal Screws: Steel & Yellow Passivated GridPro Module: GM2008PW
<b>Maximum Voltage</b>	250V~ 50Hz
<b>Load Rating</b>	20A
<b>Plate Fixing Centres</b>	60.3mm
<b>Terminal Size</b>	5mmø
<b>Terminal Torque</b>	1.2Nm
<b>Terminal Capacity</b>	3 x 2.5mm <sup>2</sup> , 2 x 4mm <sup>2</sup>
<b>Double Pole</b>	Yes
<b>Twin Earth Terminals</b>	Yes
<b>Ingress Protection</b>	IP20
<b>Back Box Depth</b>	35mm Minimum
<b>Operational Temperature</b>	-5°C to +40°C
<b>Warranty</b>	10 Years

**Standards** BS EN 60669-1:1999 +A1:2002 +A2:2008

**Additional Information**

Two keys provided (Spare keys available: SP660)  
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.  
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.