

SPECIFICATION SHEET

Product Code	FP*570#
---------------------	---------

Description	13A 2 Gang 'Ingot' Switched Socket Outlet with Single USB Charging Outlet
--------------------	---



General Information	
Dimensions	146mm x 88mm x 1.3mm (Excluding Gasket)
Finishes Available	Replace * with: BS (Brushed Steel), BN (Black Nickel), PN (Pearl Nickel), CH (Polished Chrome), SS (Stainless Steel)
Inserts Available	Replace # with: WH (White), and BK (Black). (Black Nickel finishes are supplied with black insert)
Material Composition	Rear Housing: Nylon (PA66) Front Plate: Stainless Steel Terminals: Brass Earth Strap: Mild Steel Terminal Screws: Steel and Yellow Passivated Internal Busbars: Formed Pressed Brass PCB: Mixed Components Silver "on-lay" copper/brass contacts
Back Box Depth	35mm – 47mm
Cable Size	L & N = Up to 3 x 2.5mm ² solid or stranded, or up to 2 x 4mm ² stranded conductors. Earth = Up to 3 x 1.5mm ² or 2.5mm ² solid or stranded, or up to 2=2 x 4mm ² stranded conductors
Terminal Size	Live: 5mm Neutral: 5mm Earth: 5mm
Switched	Yes
Double Pole	No (Single Pole)
Twin Earth	Yes
USB Charging Output	5V DC, 2.1A
USB Output Connector	USB Type "A"
USB Standby Current	2mA
Warranty	1 Year
Standards	
	BS 5733 (BS 1363-2) BS EN 60950-1 (USB Charger) EN 61000-6-1/3, EN 61204-3 (EMC Directive)
Additional Information	
	Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram supplied with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.