

## Technical Specification

Product Code: GM2002BTPW

Description: 20AX 2 Way Switch 'Blue' Locator Module



### General Information

<b>Dimensions</b>	24.5mm (W) x 50mm (H) x 22.5mm (D)
<b>Aperture Dimensions</b>	20mm (W) x 35mm (H)
<b>Module Frame Finish</b>	Transparent (Blue LED)
<b>Switch Finish</b>	Polar White
<b>Materials</b>	Transparent Trim: Polycarbonate Switch: Urea Rear Housing: Nylon Terminals: Brass Terminal Screws: Steel & Yellow Passivated Contacts: Silver "on-lay" Copper / Brass
<b>Maximum Voltage</b>	250V~ 50Hz
<b>Load Rating</b>	20AX (Suitable For Inductive Loads)
<b>Terminal Size</b>	5mmø
<b>Termination Type</b>	Screw
<b>Terminal Torque</b>	1.2Nm
<b>Terminal Capacity</b>	4 x 2.5mm <sup>2</sup> , 2 x 4mm <sup>2</sup>
<b>LED Indicator</b>	Yes (Blue)
<b>Back Box Depth</b>	Dependent on Plate Used
<b>Operational Temperature</b>	-5°C to +40°C
<b>Warranty</b>	10 Years (1 Year Electronics)
<b>Standards</b>	BS EN 60669-1:2018

### Additional Information

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.  
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.  
Switch LED's will turn 'ON' when the light is switched 'OFF'