

SPECIFICATION SHEET

Product Code GM2018*

Description 20A Double Pole Switch Module



| General Information | |
|-------------------------|--|
| Finishes Available | Replace * with: PW (Polar White), BK (Black), BKCH, PWCH (Chrome), BKSC, PWSC (Satin Chrome), PWBR, BKBR (Brass), BKBN (Black Nickel), BKPN, PWPN (Pearl Nickel), BKAB (Antique Brass), BKSB, PWSB (Satin Brass), BKBS, PWBS (Brushed Steel) or BKSS, PWSS (Stainless Steel) |
| Dimensions | Module Width: 24.5mm, Module Height: 50mm Aperture Width: 20mm, Aperture Height: 35mm |
| Material composition | Rocker: Urea or Urea + Stainless Steel Cover (Ingot) Cover, Insert & Rear Housing: Nylon Terminals: Brass Terminal Screws: Steel and Yellow Passivated Silver "on-lay" copper/brass contacts. |
| Voltage | 250V~ 50Hz |
| Current Rating | 20A |
| Terminal Size | 5mm Diameter |
| Torque Value | 1.2Nm |
| Cable Size | 2 x 4mm ² , 3 x 2.5mm ² or 1 x 6mm ² |
| Back Box Depth | 25mm – 47mm (Deco, Deco+, Mode, Polar) 35mm – 47mm (Define, Definity) |
| Double Pole | Yes |
| Operational Temperature | -5°C – +40°C |
| Warranty | 10 Years |

| Standards |
|---------------|
| BS EN 60669-1 |

| Additional Information |
|--|
| Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram supplied with the relevant product. These products are rated at 20A; therefore all terminals should not exceed the stated amperage. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal. |

Errors & Omissions excluded. Specification is subject to change without notice.

V1.0