

Technical Specification

Product Code: GM2018BTPW

Description: 20AX Double Pole Switch With Blue LED Indicator Module



General Information

Dimensions	24.5mm (W) x 50mm (H) x 22.5mm (D)
Aperture Dimensions	20mm (W) x 35mm (H)
Module Frame Finish	Transparent (Blue LED)
Switch Finish	Polar White
Materials	Transparent Trim: Polycarbonate Switch: Urea Rear Housing: Nylon Terminals: Brass Terminal Screws: Steel & Yellow Passivated Contacts: Silver "on-lay" Copper / Brass
Maximum Voltage	250V~ 50Hz
Load Rating	20AX (Suitable For Inductive Loads)
Terminal Size	5mmø
Termination Type	Screw
Terminal Torque	1.2Nm
Terminal Capacity	4 x 2.5mm ² , 2 x 4mm ²
LED Indicator	Yes (Blue)
Back Box Depth	Dependent on Plate Used
Operational Temperature	-5°C to +40°C
Warranty	10 Years (1 Year Electronics)
Standards	BS EN 60669-1:2018

Additional Information

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.