

Technical Specification



Product Code: GM209002BKAB

TOP

Description: 20AX 2 Way Toggle Switch Module



| General Information | | |
|----------------------------|--|--|
| Dimensions | 24.5mm (W) x 50mm (H) x 19.5mm (D) | |
| Aperture Dimensions | 20mm (W) x 35mm (H) | |
| Module Frame Finish | Black | |
| Switch Finish | Antique Brass | |
| Materials | Body & Insert: Nylon | Switch: Cast Copper |
| | Switch Cover: Stainless Steel | Terminals: Brass |
| | Terminal Screws: Steel & Yellow Passivated | Contacts: Silver "on-lay" Copper / Brass |
| Maximum Voltage | 250V 50Hz | |
| Load Rating | 20AX (Suitable For Inductive Loads) | |
| Terminal Size | 5mmø | |
| Terminal Torque | 1.2Nm | |
| Terminal Capacity | 3 x 2.5mm ² or 2 x 4mm ² | |
| Ingress Protection | IP20 | |
| Back Box Depth | Dependent On Plate Used | |
| Termination Type | Screw | |
| Operational Temperature | -5°C to +40°C | |
| Warranty | 10 Years | |
| Standards | BS EN 60669-1: 2018 | |
| Additional Information | Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal. | |

UK Design Application: GB2578427 & UK Design Registration: 3015621

Scolmore Park, Landsberg, Lichfield Road Industrial Estate, Tamworth, Staffordshire, B79 7XB United Kingdom **T:** +44 (0)1827 63454 | **F:** +44 (0)1827 63362 **E:** sales@scolmore.com | **W:** scolmore.com

Page 1 of 1 Rev.1.0 Errors & Omissions excluded. Specification is subject to change without notice.