

**Technical Specification**

**Product Code:** GM209002BKSC

**Description:** 20AX 2 Way Toggle Switch Module



**General Information**

<b>Dimensions</b>	24.5mm (W) x 50mm (H) x 19.5mm (D)	
<b>Aperture Dimensions</b>	20mm (W) x 35mm (H)	
<b>Module Frame Finish</b>	Black	
<b>Switch Finish</b>	Satin Chrome	
<b>Materials</b>	Body & Insert: Nylon	Switch: Cast Copper
	Switch Cover: Stainless Steel	Terminals: Brass
	Terminal Screws: Steel & Yellow Passivated	Contacts: Silver "on-lay" Copper / Brass
<b>Maximum Voltage</b>	250V 50Hz	
<b>Load Rating</b>	20AX (Suitable For Inductive Loads)	
<b>Terminal Size</b>	5mmø	
<b>Terminal Torque</b>	1.2Nm	
<b>Terminal Capacity</b>	3 x 2.5mm <sup>2</sup> or 2 x 4mm <sup>2</sup>	
<b>Ingress Protection</b>	IP20	
<b>Back Box Depth</b>	Dependent On Plate Used	
<b>Termination Type</b>	Screw	
<b>Operational Temperature</b>	-5°C to +40°C	
<b>Warranty</b>	10 Years	
<b>Standards</b>	BS EN 60669-1: 2018	

**Additional Information**

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.  
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

UK Design Application: GB2578427 & UK Design Registration: 3015621