


Technical Specification

Product Code: GM209028BKAB

Description: 20AX Intermediate Toggle Switch Module



General Information

Dimensions	24.5mm (W) x 50mm (H) x 19.5mm (D)	
Aperture Dimensions	20mm (W) x 35mm (H)	
Module Frame Finish	Black	
Switch Finish	Antique Brass	
Materials	Body & Insert: Nylon	Switch: Cast Copper
	Switch Cover: Stainless Steel	Terminals: Brass
	Terminal Screws: Steel & Yellow Passivated	Contacts: Silver "on-lay" Copper / Brass
Maximum Voltage	250V 50Hz	
Load Rating	20AX (Suitable For Inductive Loads)	
Terminal Size	5mmø	
Terminal Torque	1.2Nm	
Terminal Capacity	3 x 2.5mm ² or 2 x 4mm ²	
Ingress Protection	IP20	
Back Box Depth	Dependent On Plate Used	
Termination Type	Screw	
Operational Temperature	-5°C to +40°C	
Warranty	10 Years	
Standards	BS EN 60669-1: 2018	

Additional Information

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

UK Design Application: GB2578427 & UK Design Registration: 3015621