

Technical Specification

Product Code: GM209028PWPN

Description: 20AX Intermediate Toggle Switch Module



General Information

| | | |
|--------------------------------|--|--|
| Dimensions | 24.5mm (W) x 50mm (H) x 19.5mm (D) | |
| Aperture Dimensions | 20mm (W) x 35mm (H) | |
| Module Frame Finish | Polar White | |
| Switch Finish | Pearl Nickel | |
| Materials | Body & Insert: Nylon | Switch: Cast Copper |
| | Switch Cover: Stainless Steel | Terminals: Brass |
| | Terminal Screws: Steel & Yellow Passivated | Contacts: Silver "on-lay" Copper / Brass |
| Maximum Voltage | 250V 50Hz | |
| Load Rating | 20AX (Suitable For Inductive Loads) | |
| Terminal Size | 5mmø | |
| Terminal Torque | 1.2Nm | |
| Terminal Capacity | 3 x 2.5mm ² or 2 x 4mm ² | |
| Ingress Protection | IP20 | |
| Back Box Depth | Dependent On Plate Used | |
| Termination Type | Screw | |
| Operational Temperature | -5°C to +40°C | |
| Warranty | 10 Years | |
| Standards | BS EN 60669-1: 2018 | |

Additional Information

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

UK Design Application: GB2578427