



Product Code: MM047WH		Description: 13A Fused Connection Module		
			CLICES LOBT BS 5733 13A 2809- LIB 0 4.7	
General In	formation			
Dimensions (mm)		25 (W) x 50 (H) x 24.7 (D)		
Finish		Polar White		
Materials		Cover & Housing: Polycarbonate	Terminals: Brass	
		Terminal Screws: Steel & Yellow Passivated	Internal Busbars: Formed Pressed Brass	
Anti Microbial Certified		No		
Rated Voltage (V~) (Ue)		250	Frequency (Hz) 50	
Resistive Load Rating (A)		13		
Fuse Fitted Rating & Type		13A (BS 1362)		
Termination Type		Screw		
Terminal Size (mm)			al Torque Value (Nm) 1.8	
Terminal Capacity - Solid (mm ²)		4 x 1.5 or 3 x 2.5		
Product Marking		Fused Symbol		
Minimum Back Box Depth (mm)		25 (35 Flat Plate)		
Ingress Protection				
Operational Temperature (°C) Warranty (Years)		-5 to +40		
		1		
Additional Informatio	Ensure t diagram	For cleaning / polishing of products, use only a soft, dry, clean cloth. Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.		

Scolmore House, Mariner, Lichfield Road Industrial Estate, Tamworth, Staffordshire, B79 7UL United Kingdom T: +44 (0)1827 63454 | F: +44 (0)1827 63362 E: sales@scolmore.com | W: scolmore.com