

Product Code: MM620BK

Description: 10A/6AX Key Card Switch Engine Module



### General Information

Dimension Without Front Clips (mm)	50 (W) x 50 (H) x 32.5 (D)	
Overall Dimensions (mm)	50 (W) x 50 (H) x 40 (D)	
<b>Materials</b>	Cover & Housing: Polycarbonate	Terminals & Screws: Brass
	PCB: Electronic Components	
Anti Microbial Certified	No	
Rated Voltage (V~) (Ue)	230	Frequency (Hz) 50
Resistive Load Rating (A)	10	
Inductive Load Rating (AX)	6	
Termination Type	Screw	
Terminal Size (mm)	Ø3.5	Terminal Torque Value (Nm) 0.5
Terminal Capacity - Solid (mm²)	2 x 1.5	
Time Delay Settings	10 Seconds To 5 Minutes (Activates Once Key Is Removed)	
1 Way Switch	Yes	
Single Pole Switched	Yes	
LED Indicator	Yes	Indicator Colour Blue
LED Indicator Status	Only illuminates when switch is OFF	
Minimum Back Box Depth (mm)	35 (47 Flat Plate)	
Ingress Protection	IP20	
Operational Temperature (°C)	-5 to +40	
Warranty (Years)	1	

### Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.  
 The module is not supplied with key card, cover fascia or mounting plate.  
 Ensure the required fascia is ordered, see SP620 fascia range.  
 The module will fit in to a Euro module 50mm x 50mm aperture (311 plate)  
 Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.  
 Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.