

Product Code: OA036AG

Description: 2 Gang 13A DP IP66 Weatherproof Switched Socket Unit



General Information

Dimensions	158mm (W) x 158mm (H) x 90mm (D)	
External Finish	Anthracite Grey	
Socket Finish	Anthracite Grey With White Inboard Switches	
Materials	Cover, Housing & Clip: Polycarbonate	Seal & Gasket: Rubber
	Accessory Plate & Housing: Urea	Terminals: Brass
	Terminal Screws: Steel & Yellow Passivated	Contacts: Silver "on-lay" Copper / Brass
	Internal Busbars: Formed Pressed Brass	Earth Strap: Mild Steel
Maximum Voltage	250V~ 50Hz	
Load Rating	13A	
Accessory Fixing Centres	120.6mm	
Terminal Size	5mmø	
Terminal Torque	2.0Nm	
Terminal Capacity	3 x 2.5mm ² or 2 x 4mm ²	
Lockable Cover	Yes (Lock Not Supplied)	
Switched	Yes (Inboard Rockers)	
Double Pole	Yes	
Twin Earth Terminals	Yes	
Ingress Protection	IP66	
Termination Type	Screw	
Back Box Knockouts	7 x 20mmø	
Operational Temperature	-5°C to +40°C	
Warranty	5 Years	
Standards	BS 1363-2: 2016 +A1: 2018 BS EN 60529:1992+A2:2013 (Sections 13 & 14)	

Additional Information

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

All grey & white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases as well as anti-viral properties against enveloped and non-enveloped viruses.

All products have been independently tested with 99.9% of enveloped viruses and 92% of non-enveloped viruses killed off whilst achieving a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.