



## List No. NMT2SPD3W/1

NH / NM / NMX

Type 2 Miniature SPD Kit



- Type 2 SPD kit
- For Wylex consumer units
- DIN rail mounting, single module, including all connections
- Status indication and volt free contact for remote monitoring
- Replacement protective element (cartridge) is available, NMT2SPD/P

### Product Specification Data

System configuration TN-C-S	Yes
System configuration TN-S	Yes
System configuration TT	Yes
Nominal discharge surge current (8/20)	20 kA
Short-circuit breaking capacity (I <sub>sc</sub> )	25 kA
Max. continuous voltage AC	275 V
Max. discharge surge current (8/20)	40 kA
Mounting method	DIN rail (top hat rail) 35 mm
Construction size	1 modular spacing
Voltage protection level	1.3 kV
Max. conductor cross section solid (solid, stranded)	25 mm <sup>2</sup>
Voltage protection level L-N	1.3 kV
Voltage protection level N-PE	1.3 kV
With remote signalling contact	Yes
Integrated backup fuse	No
Category type 2	Yes
Degree of protection (IP)	IP20
Product Standard/s	IEC EN 61643-11
Frequency	50 Hz
CE Mark	Yes
WEEE Symbol	Yes
Height	85 mm
Width	18 mm
Depth	70 mm