



**NMT2SPD3W/1**



**NMT2SPD/P**

### SURGE PROTECTION DEVICE

CAT REF	DESCRIPTION
<b>NMT2SPD3W/1</b>	Single Module Type 2 SPD

- Suitable for all Single Phase 3 Wire Systems TN-C-S, TN-S and TT
- Clear Indication of device status
- Fitted with remote signalling contact
- Suitable for use in Main Switch, Split Load & Hi-Integrity consumer unit configurations
- Not suitable for Dual RCD configurations

Alternative SPD products are available for Dual RCD consumer unit installations. Please contact Wylex technical for further assistance.

### TECHNICAL DATA

<b>Product Standard</b>	IEC EN 61643-11
<b>Nominal discharge surge current (8/20) <math>\mu</math>s</b>	20kA
<b>Short-circuit breaking capacity (I<sub>sc</sub>cr)</b>	25kA
<b>Max. continuous voltage AC</b>	275V
<b>Max. discharge surge current (8/20) <math>\mu</math>s</b>	40kA
<b>Voltage protection level</b>	1.3 kV
<b>Voltage protection level L-N</b>	1.3 kV
<b>Voltage protection level N-PE</b>	1.3 kV
<b>Max. conductor cross section (solid / stranded)</b>	25mm <sup>2</sup>
<b>Degree of protection</b>	IP20
<b>Dimensions</b>	Height 85mm x Width 18mm x Depth 70mm

### REPLACEMENT PLUG-IN CARTRIDGE

CAT REF	DESCRIPTION
<b>NMT2SPD/P</b>	Replacement Plug-in Cartridge for <b>NMT2SPD3W/1</b>

- Combined Metal Oxide Varistor (L1 & N) and Gas Discharge Tube (N & E)