



List No. REC2STT

Enclosed, Slimline Insulated, 100A DP Twin Terminal Supply Isolator with Allen Key Screw Heads



- 100A Double pole switch disconnecter
- Twin terminal (3mm hex allen key screw heads)
- Slimline 3 part seal and secure enclosure
- Lockable switch handle

Product Specification Data

Revision Date: 15/10/2021

Version as main switch	No
Version as maintenance-/service switch	Yes
Max. rated operation voltage Ue AC	400 V
Rated operating voltage	230-400 V
Rated permanent current Iu	100 A
Conditioned rated short-circuit current Iq	16 kA
Number of poles	2
Motor drive optional	No
Voltage release optional	No
Suitable for distribution board installation	No
Type of control element	Toggle
Interlockable	No
Type of electrical connection of main circuit	Screw connection
Degree of protection (IP), front side	IP20
Product Standard/s	BS EN 60947-3
Terminal Capacity L&N	50 mm ²
CE Conformity	Yes
WEEE Symbol	Yes
UKCA Conformity	Yes
Height	149 mm
Width	63 mm
Depth	63 mm

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.