

NEBRASKA

IP65 LED slim emergency bulkhead with a range of attachments



STANDARD LEGENDS AVAILABLE AS UP, DOWN, LEFT & RIGHT



"MAN RUNNING THROUGH DOOR" V2 LEGENDS AVAILABLE AS UP, DOWN, LEFT & RIGHT



NEBRASKA HINGED GEAR TRAY WITH QUICK-RELEASE CATCHES



NEBRASKA SEMI-RECESSED MOUNTING KIT

SCAN FOR DIGITAL COPY



APPLICATIONS

- Corridors
- Exits
- Escape routes

CONSTRUCTION

- Polycarbonate base and cover
- Cover fitted to base with stainless steel screws in threaded brass inserts
- Hinged gear tray
- Supplied with standard ("Man running towards door") legend pack.
- 20mm conduit entry
- NiCd battery cells (not suitable for use below 0°C)

TECHNICAL DETAILS

- 175 lm on mains
- 133 lm on battery supply
- 3.8W
- 3 hours operation on battery power after mains failure
- 20m maximum viewing distance with standard legends
- 30m maximum viewing distance with drop-down attachment
- Self-test version, compliant with BS5266 available. Suffix STM3 as listed
- All variants can be installed as maintained or non-maintained. Wiring diagrams are supplied in the instruction leaflet.

OPTIONS

DROP DOWN ATTACHMENT

Polycarbonate drop down signage attachment available, c/w legends. Order as separate item.

RECESSED MOUNTING KIT Semi-recessed mounting kit available. Cut-out 360 x 120mm. Order as a separate item.


LEGENDS Spare legend packs available.

Alternative legend pack available as listed - to be ordered as a separate item.

For "man running through door", use suffix V2, as listed.

ORDER CODE	DESCRIPTION
NNE/2/LED/M3/V3	Nebraska V3 2W LED IP65 Maint. 3Hr
NNE/2/LED/STM3/V3	Nebraska V3 2W LED IP65 Maint. 3Hr Self Test
ATTACHMENTS	
NNE/DDA/V3	Nebraska Drop Down Attachment C/W Legend Packs
NNE/RMK/V3	Nebraska V3 Recessed Mounting Kit
NNE/V2/LEP4	Nebraska V2 Legend Pack Of Up Down Left Right
NNELEP4	Nebraska Legend Pack Of Up Down Left Right

NEBRASKA WITH DROP DOWN ATTACHMENT



NEBRASKA

